



PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA20485	CHROMEL / ALUMEL	K
FA20485-02	IRON / CONSTANTAN	J
FA20485-03	TUNGSTEN / RHENIUM*	C
FA20485-04	CHROMEL / CONSTANTAN	E

* TYPE C USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

*FOR INTERNALE PRESSURE 5 TO 100 PSIG
 AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: ONE PAIR T/C SPADE TYPE FEEDTHRU		 SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA20485SL REV. A2
REV. APP'D DATE SCALE 1:1 DIMENSIONS IN INCHES [mm]	DRAWN JS 8/3/2009	ENG APPR. MH 08/07/2009	PART NO. (SEE TABLE) REV. A						

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.