

PART NO.	AIR SIDE PLUG
FA20606	NO
KT20606	YES


DATINICS				
RATINGS				
VOLTAGE:	10KV DC			
CURRENT:	8.2 AMPS			
PRESSURE:	120 PSIG @ 20°C			
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C			
TEMPERATURE WITH PLUG:	-55°C TO 85°C			

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN
A2	JS	10/22/2012	CO\$10019-11	INCHES [mm]

THIRD ANGLE PROJECTION



N	DRAWN	JS	3/24/2009
]	ENG APPR.	MH	06/12/2009

TITLE:

TWO 10KV RECESSED SHVS

PART NO. FA20606 REV. A



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA20606SL REV. A2