

PART NO.	AIR SIDE PLUG
FA20722	NO
KT20722	YES


RATINGS			
VOLTAGE:	10KV DC		
CURRENT:	8.2 AMPS		
PRESSURE:	120 PSIG @ 20°C		
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C		
TEMPERATURE WITH PLUG:	-55°C TO 85°C		

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN
A2	JS	10/22/2012	CO\$10016-14	INCHES [mm]

THIRD ANGLE PROJECTION



N	DRAWN	JS	3/19/2009
]	ENG APPR.	MH	06/12/2009

TITLE:

FOUR 10KV EXPOSED SHVS

PART NO. FA20722 REV. A



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA20722SL REV. A2