


PART NO.	AIR SIDE PLUG
FA20765	NO
KT20765	YES

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	10 AMPS
PRESSURE:	1600 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-260°C TO 230°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

5KV SHV CONNECTOR IN NPT

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 2.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	4/1/2009
A1	MH	06/12/2009	COS50031-11		ENG APPR.	MH	06/12/2009

PART NO. FA20765 REV. A

SALES DWG NO. FA20765SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.