

| | |
|----------|---------------|
| PART NO. | AIR SIDE PLUG |
| FA20774 | NO |
| KT20774 | YES |

| RATINGS | |
|---------------------------|----------------|
| VOLTAGE: | 10KV DC |
| CURRENT: | 8.2 AMPS |
| PRESSURE: | 0 PSIG @ 20°C* |
| TEMPERATURE WITHOUT PLUG: | -25°C TO 205°C |
| TEMPERATURE WITH PLUG: | -25°C TO 85°C |

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA20774SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 10KV RECESSED SHVS

PART NO. FA20774 REV. A

| REV. | APP'D | DATE | SCALE 4:5 | DIMENSIONS IN INCHES [mm] | DRAWN | JS | 3/30/2009 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A2 | JS | 10/22/2012 | COS10020-12 | | ENG APPR. | MH | 06/12/2009 |