



PART NO.	AIR SIDE PLUG
FA20837	NO
KT20837	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	0.8 AMPS
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUGS:	-269°C TO 350°C
TEMPERATURE WITH PLUGS:	-65°C TO 165°C

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</p>				<p>THIRD ANGLE PROJECTION</p> 		<p>TITLE</p> <p>DOUBLE ENDED 50 OHM BNC</p>			 <p>SOLID SEALING TECHNOLOGY</p>	
REV.	APP'D	DATE	SCALE 2.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	4/9/2009	PART NO. FA20837 REV. B	WWW.SOLIDSEALING.COM	
B1	CW	1/11/2024	COBN0051-11		ENG APPR.	MH	06/12/2009		SALES DWG NO. FA20837SL REV. B1	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.