



PART NO.	AIR SIDE PLUG
FA20839	NO
KT20839	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	0.8 AMPS
PRESSURE:	0 PSIG @ 20°C
TEMPERATURE WITHOUT PLUGS:	-25°C TO 205°C
TEMPERATURE WITH PLUGS:	-25°C TO 165°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE DBL END 50 OHM BNC			
REV.	APP'D	DATE	SCALE 1.75:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	4/13/2009	PART NO. FA20839 REV. A	
A3	CW	1/11/2024	COBN0051-12		ENG APPR.	MH	06/12/2009		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.