

MATES WITH STANDARD USB SERIES "A" RECEPTACLE, BOTH ENDS

USB SERIES "A" PLUG CONFIGURATION, BOTH ENDS

1.33 CF SEAL SIDE

Ø.56 [14.3]

.3 [8]

1.1 [27]

1.1 [27]

RATINGS


VOLTAGE	30V RMS
CURRENT	1 AMP
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE WITHOUT RECEPTACLES ATTACHED	-269°C TO 200°C

OUR USB CONNECTORS MEET OR EXCEED THE VOLTAGE AND CURRENT REQUIREMENTS FOR USB 2.0 AND 3.0. WE DO NOT GUARANTEE THE DATA TRANSFER RATE OR ANY OTHER REQUIREMENT OF THE USB SPECIFICATIONS.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

USB CONNECTOR



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	OG	06/02/2009
B3	JS	09/13/2013	MPC10289-12		ENG APPR.	OG	06/11/2009

PART NO. FA21048 REV. B

SALES DWG NO. FA21048SL REV. B3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.