



PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA21116	CHROMEL / ALUMEL	K
FA21116-02	IRON / CONSTANTAN	J
FA21116-03	TUNGSTEN / RHENIUM*	C
FA21116-04	CHROMEL / CONSTANTAN	E

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

\* TYPE C USES COMPENSATING WIRE  
 MAXIMUM JUNCTION TEMPERATURE 250°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE ONE PR T/C SPADE TYPE BASEPLATE			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	6/1/2009	PART NO. (SEE TABLE) REV. C	WWW.SOLIDSEALING.COM
C1	CW	4/11/2022	MPCL0290-1ST		ENG APPR.	MH	06/01/2009		SALES DWG NO. FA21116SL REV. C1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**