


RATINGS	
VOLTAGE:	1KV DC
CURRENT:	2 AMPS
TEMPERATURE:	-40°C TO 75°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

MICRODOT AIR SIDE
PLUG & CABLE



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	7/7/2009
B1	JS	02/16/2012	MACA0001-12		ENG APPR.	MH	08/07/2009

PART NO. FA21382 REV. B

SALES DWG NO. FA21382SL REV. B1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.