



PART NO.	AIR SIDE PLUG
FA22052	NO
KT22052	YES

PERFORMANCE SPECIFICATIONS	
PIN / SHIELD VOLTAGE (DWV):	500V DC
SHIELD / GROUND VOLTAGE (DWV):	2.5KV DC
CURRENT:	0.8 AMPS
PRESSURE:	300 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-80°C TO 450°C*
TEMPERATURE WITH PLUG:	-65°C TO 165°C

*CONTACT SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA22052SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FLOATING 50 OHM SMA

PART NO. FA22052 REV. A

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	04/15/2016
A1	JF	04/15/2016	COSA0007-03		ENG APPR.	JF	04/15/2016

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.