


RATINGS	
VOLTAGE:	125KV DC
CURRENT:	100 AMPS
TEMPERATURE:	-55°C TO 450°C

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE  
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY  
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN  
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

125KV FEEDTHRU

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:2	DIMENSIONS IN INCHES [mm]	DRAWN	JS	06/24/2011
A1	JS	04/17/2012	FTFL0038-11		ENG APPR.	JS	04/17/2012

PART NO. FA22278 REV. A

SALES DWG NO. FA22278SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**