



PART NO.	AIR SIDE PLUG
FA23247	NO
KT23247	YES

RATINGS	
VOLTAGE:	1.5KV DC
CURRENT:	5 AMPS
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-80°C TO 450°C*
TEMPERATURE WITH PLUG:	-65°C TO 165°C

*CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM

<div>PROPRIETARY AND CONFIDENTIAL</div> <div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</div>					<div>THIRD ANGLE PROJECTION</div> <div></div>			<div>TITLE:</div> <div>50 OHM TYPE N DOUBLE ENDED</div>		<div></div> <div>SOLID SEALING TECHNOLOGY, INC.</div>	
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	07/14/2010	PART NO. FA23247 REV. B		SALES DWG NO. FA23247SL REV. B1	
B1	JS	10/19/2012	COTN0025-16		ENG APPR.	JS	07/14/2010				

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.