	Ø.870±.002[22.10= 020[0.51] WELD 	-
PART NO. AIR SIDE PLUG	RA	TINGS
FA23436 NO	VOLTAGE:	1.5KV DC
KT23436 YES	CURRENT:	1 AMP
	PRESSURE:	500 PSIG @ 20°C
	TEMPERATURE WITHOUT PLUG:	-269°C TO 350°C
	TEMPERATURE WITH PLUG:	-65°C TO 165°C

## WWW.SOLIDSEALING.COM

	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION			TITLE: TYPE N 50 OHM CONNECTOR	
REV.	APP'D	DATE	SCALE 2.25:1	DIMENSIONS IN	DRAWN	JS	09/26/2013	PART NO. FA23436 REV. A	SOLID SEALING TECHNOLOGY, INC.
A2	JF	05/22/2015	COTN0003-01	INCHES [mm]	ENG APPR.	JS	09/26/2013	TARTINO, TAZJ430 REV.A	SALES DWG NO. FA23436SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.