


PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-269°C TO 200°C

CONTACT MATERIAL	LOCATIONS:
CHROMEL (+)	A,C,E
ALUMEL (-)	B,D,F

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE

TYPE K 3 PAIR VACUUM SIDE PLUG



REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/14/2020
A1	JF	9/14/2020	MSME0034-12		ENG APPR.	JF	9/14/2020

PART NO. FA23459 REV. A

WWW.SOLIDSEALING.COM

SALES DWG NO. FA23459SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**