



+ CONDUCTOR LOCATIONS: A,C,E
 - CONDUCTOR LOCATIONS: B,D,F

PLUGS SOLD SEPARATELY:
 - AIR SIDE PLUG W/CRIMP CONTACTS: FA41396
 - VACUUM SIDE PEEK PLUG: FA23459

PERFORMANCE SPECIFICATIONS	
CONDUCTOR MATERIAL:	(+)CHROMEL / (-)ALUMEL
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 3 PAIR T/C TYPE K CONNECTOR			
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	07/23/2010	PART NO. FA23474 REV. A WWW.SOLIDSEALING.COM	
A3	JF	9/4/2020	MPCL0161-14SL		ENG APPR.	JS	07/23/2010		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.