



PERFORMANCE SPECIFICATION	
VOLTAGE:	1KV DC
CURRENT:	1.1 AMPS
PRESSURE:	3500 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

WWW.SOLIDSEALING.COM

<div>PROPRIETARY AND CONFIDENTIAL</div> <div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</div>					<div>THIRD ANGLE PROJECTION</div> <div></div>			<div>TITLE:</div> <div>BASEPLATE FEEDTHRU</div>		<div></div> <div>SOLID SEALING TECHNOLOGY, INC.</div>	
REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN INCHES [mm]	DRAWN	ET	05/17/2018	PART NO. FA23878 REV. A		SALES DWG NO. FA23878SL REV. A1	
A1	JF	03/12/2019	FTCL0163-11		ENG APPR.	JF	03/12/2019				

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.