



PLUGS SOLD SEPARATELY:  
-VACUUM SIDE PEEK PLUG FA13606  
-AIR SIDE PLUG KT14879

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500 V DC
CURRENT:	3 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

\*FOR INTERNAL PRESSURE 5 TO 100 PSIG  
AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE <b>(2) 50 PIN SUB-D CONNECTORS</b>			
REV.	APP'D	DATE	SCALE 2:3	DIMENSIONS IN INCHES [mm]	DRAWN	JF	05/21/2014	PART NO. FA24018 REV. B WWW.SOLIDSEALING.COM	
B1	CW	4/14/2022	MPCL0504-11		ENG APPR.	JF	05/21/2014		

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**