


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA25363	COPPER	27 AMPS
FA25363-02	MOLYBDENUM	13.5 AMPS
FA25363-03	NICKEL	8.2 AMPS
FA25363-04	304 STN STL	1.8 AMPS

RATINGS	
VOLTAGE:	2KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 2KV BASEPLATE FEEDTHRUS

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	JS	09/14/2011
A1	JS	09/14/2011	MPCL0162-2ST		ENG APPR.	JS	09/14/2011

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA25363SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.