



| | |
|----------|---------------|
| PART NO. | AIR SIDE PLUG |
| FA25374 | NO |
| KT25374 | YES |

| RATINGS | |
|---------------------------|----------------|
| VOLTAGE: | 20KV DC |
| CURRENT: | 16.5 AMPS |
| PRESSURE: | 0 PSIG @ 20°C* |
| TEMPERATURE WITHOUT PLUG: | -25°C TO 205°C |
| TEMPERATURE WITH PLUG: | -25°C TO 85°C |

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA25374SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

20 KV SHV EXPOSED ON KF16

PART NO. FA25374 REV. A

| REV. | APP'D | DATE | SCALE 3:2 | DIMENSIONS IN INCHES [mm] | DRAWN | JS | 09/16/2011 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A2 | JF | 03/24/2014 | COS20002-08 | | ENG APPR. | JS | 09/16/2011 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.