

PART NO.	AIR SIDE PLUG	
FA25858	NO	
KT25858	YES	


RATINGS			
VOLTAGE:	500V DC		
CURRENT:	1.8 AMPS		
PRESSURE:	4000 PSIG @ 20°C		
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C		
TEMPERATURE WITH PLUG:	-65°C TO 165°C		

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN
Al	JS	04/16/2013	COSA0054-11	INCHES [mm]

THIRD ANGLE PROJECTION



IN	DRAWN	JS	04/16/2013		
1]	ENG APPR.	JS	04/16/2013		

TITLE:

SMA CONNECTOR

PART NO. FA25858 REV. A



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA25858SL REV. A1