


PART No.	AIR SIDE PLUG
FA26378	NO
KT26378	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	1.5 KV DC
CURRENT:	1 AMP
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 350°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE
 TYPE N 50 OHM CONNECTOR



REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	04/12/2012
C1	CW	5/11/2023	COTN0002-01		ENG APPR.	MH	04/12/2012

PART NO. FA26378 REV. C

WWW.SOLIDSEALING.COM

SALES DWG NO. FA26378SL REV. C1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.