

RATINGS	
VOLTAGE:	375V DC
CURRENT:	1 AMP
PRESSURE:	1300 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C


WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA26702SL REV. B1

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE:
 25 PIN MICRO D CONNECTOR

PART NO. FA26702 REV. B

REV.	APP'D	DATE	SCALE 3:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	06/15/2012
B1	OG	02/09/2015	MPCL0413-11		ENG APPR.	JS	06/15/2012

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.