



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA26715	COPPER	16 AMPS
FA26715-02	MOLYBDENUM	8.5 AMPS
FA26715-03	NICKEL	5 AMPS
FA26715-04	304 STN STL	1.1 AMPS

RATINGS	
VOLTAGE:	2KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1400 PSI @ 20°C
TEMPERATURE:	-80°C TO 450°C*

* CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: FOUR 2KV FEEDTHROUGHS		
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	06/21/2012	PART NO. (SEE TABLE) REV. A	
A1	JS	06/21/2012	MPCLO410-1ST		ENG APPR.	JS	06/21/2012		SALES DWG NO. FA26715SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.