



PERFORMANCE SPECIFICATIONS	
# OF CONDUCTORS	37
VOTLAGE:	300V RMS
TEMPERATURE:	-65°C TO 200°C

DETAIL A
SCALE 6 : 1

*CABLE IS AVAILABLE IN ANY LENGTH, PART NUMBER SUFFIX INDICATES LENGTH IN INCHES.

EXAMPLE: FA27826-036 IS A 36 INCH LONG CABLE

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 37 PIN SUB-D RIBBON CABLE			
REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	4/7/2021	PART NO. FA27826 REV. A	WWW.SOLIDSEALING.COM
A1	JF	4/7/2021	AHDWR020-11		ENG APPR.	JF	4/7/2021		SALES DWG NO. FA27826SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.