

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	2KV DC
CURRENT:	55 AMPS
WORKING PRESSURE:	3200 PSIG @ 20°C
BURST PRESSURE:	9500 PSIG @ 20°C
TEMPERATURE:	-80°C TO 230°C*

*CALL SST TO CONFIRM LOWER TEMPERATURE USE

**AVAILABLE WITH CUSTOM CONDUCTOR LENGTHS

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA28677SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

2KV PRESSURE FEEDTHROUGH

PART NO. FA28677 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	01/24/2018
A1	JF	01/24/2018	FTST0169-11		ENG APPR.	JF	01/24/2018

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.