

PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA29169	COPPER	100 AMPS	185 AMPS
FA29169-02	MOLYBDENUM	93 AMPS	93 AMPS
FA29169-03	NICKEL 200	56 AMPS	56 AMPS
FA29169-04	304 STN STL	12 AMPS	12 AMPS

PERFORMANCE SPECIFICATIONS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE (DWV):	25KV DC	12KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	750 PSIG @ 20°C	750 PSIG @ 20°C
TEMPERATURE:	-40°C TO 125°C	-269°C TO 450°C

MATES WITH POWERPLUG FA18649

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA29169SL REV. A3

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

25KV FEEDTHRU

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	09/20/2013
A3	JF	1/29/2016	FTST0081-2ST		ENG APPR.	JS	09/20/2013

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.