



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUGS
FA29400	COPPER	100 AMPS	185 AMPS
FA29400-02	MOLYBDENUM	93 AMPS	93 AMPS
FA29400-03	NICKEL	56 AMPS	56 AMPS
FA29400-04	304 STN STL	12 AMPS	12 AMPS

PERFORMANCE SPECIFICATIONS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE (DWV):	15KV DC	12KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 125°C	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

MATES WITH POWERPLUG FA18649

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE TWO 12KV FEEDTHROUGHS			
REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	JS	11/05/2013	PART NO. (SEE TABLE) REV. C WWW.SOLIDSEALING.COM	
C2	JF	08/22/2024	FTST0175-1ST		ENG APPR.	JS	11/05/2013		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.