



PART NO.	AIR SIDE PLUG
FA29843	NO
KT29843	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE (DWV):	7KV DC
OPERATING VOLTAGE:	1.5KV DC*
CURRENT:	7 AMPS
PRESSURE:	0 PSIG @ 20°C**
TEMPERATURE WITHOUT PLUG:	-25°C TO 150°C***
TEMPERATURE WITH PLUG:	-25°C TO 165°C

*BASED ON AIR SIDE PLUG

**FOR INTERNAL PRESSURE 5 TO 100 PSIG
AN OVERPRESSURE RING IS REQUIRED.

***200°C SHORT TERM 150° CONTINUOUS

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				 THIRD ANGLE PROJECTION		TITLE 50 OHM HN CONNECTOR				 SOLID SEALING TECHNOLOGY	
REV.	APP'D	DATE	SCALE 5:4	DIMENSIONS IN INCHES [mm]	DRAWN	JF	01/28/2014	PART NO. FA29843 REV. A	WWW.SOLIDSEALING.COM		
A3	JF	02/24/2025	COHN0013-11		ENG APPR.	JF	01/28/2014		SALES DWG NO. FA29843SL REV. A3		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.