

|          |               |
|----------|---------------|
| PART NO. | AIR SIDE PLUG |
| FA29863  | NO            |
| KT29863  | YES           |

| RATINGS                   |                |
|---------------------------|----------------|
| VOLTAGE:                  | 1.5 KV DC      |
| CURRENT:                  | 1 AMP          |
| PRESSURE:                 | 0 PSIG @ 20°C* |
| TEMPERATURE WITHOUT PLUG: | -25°C TO 205°C |
| TEMPERATURE WITH PLUG:    | -25°C TO 165°C |


\*FOR INTERNAL PRESSURE 5 TO 100 PSIG  
AN OVERPRESSURE RING IS REQUIRED

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TYPE N CONNECTOR



**SOLID SEALING TECHNOLOGY, INC.**

|      |       |           |              |                           |           |    |           |
|------|-------|-----------|--------------|---------------------------|-----------|----|-----------|
| REV. | APP'D | DATE      | SCALE 1.25:1 | DIMENSIONS IN INCHES [mm] | DRAWN     | MH | 8/18/2017 |
| A1   | MH    | 8/18/2017 | COTN0049-21  |                           | ENG APPR. | MH | 8/18/2017 |

PART NO. FA29863 REV. A

SALES DWG NO. FA29863SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**