



PART NO.	CONDUCTOR MATERIAL	W WALL
FA30098	COPPER	.032[0.81]
FA30098-02	304 STN STL	.035[0.89]

PERFORMANCE SPECIFICATION	
VOLTAGE:	8KV DC
PRESSURE:	0 PSIG @ 20°C**
TEMPERATURE:	-80°C TO 450°C*

\* CALL SST TO CONFIRM LOWER TEMPERATURE USE  
 \*\* FOR INTERNAL PRESSURE 5 TO 100 PSIG  
 AN OVER PRESSURE RING IS REQUIRED

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE <b>8KV FEEDTHROUGH</b>			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	3/21/2014	PART NO. (SEE TABLE) REV. B	WWW.SOLIDSEALING.COM
B1	JF	11/09/2023	FTCL0225-1ST		ENG APPR.	MH	3/21/2014		SALES DWG NO. FA30098SL REV. B1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**