

PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA30272	CHROMEL / ALUMEL	K
FA30272-02	IRON / CONSTANTAN	J
FA30272-03	TUNGSTEN / RHENIUM*	C
FA30272-04	CHROMEL / CONSTANTAN	E

\*TYPE C USES COMPENSATING WIRE  
MAXIMUM JUNCTION TEMPERATURE 250°C


PERFORMANCE SPECIFICATIONS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

\*FOR INTERNAL PRESSURE 5 TO 100 PSIG  
AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO PAIR SPADE TYPE FEEDTHRU

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	05/22/2017
A1	JF	05/22/2017	MPCLO031-6ST		ENG APPR.	JF	05/22/2017

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA30272SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**