



PLUGS SOLD SEPARATELY  
 9 PIN AIR SIDE PLUG: FA13603  
 9 PIN VACUUM SIDE PLUG: KT14876

15 PIN AIR SIDE PLUG: FA13604  
 15 PIN VACUUM SIDE PLUG: KT14877

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500 V DC
CURRENT:	5 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

\*FOR INTERNAL PRESSURE 5 TO 100 PSIG  
 AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 9 PIN SUB D, 15 PIN SUB D IN ISO 63			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	08/18/2023	PART NO. FA30778 REV. A WWW.SOLIDSEALING.COM	
A1	JF	08/18/2023	MPC10508-11		ENG APPR.	JF	08/18/2023		

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**