



PERFORMANCE SPECIFICATIONS	
VOLTAGE	2700VRMS*
TEMPERATURE	-269°C TO 200°C (HIGH TEMP IS WITH SOCKETS INSTALLED AND LIMITED TO 1HR. CONSULT SST IF HIGHER TEMP BAKE OUT IS NEEDED)
LEAK RATE	<1 X 10E-10 ATM-CC/SEC (He)

\* VOLTAGE PERFORMANCE LIMITED BY STANDARD 7/16 COAXIAL PLUG.

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</p>				<p>THIRD ANGLE PROJECTION</p> 		<p>TITLE</p> <p>50 OHM DBL END 7/16 CONNECTOR</p>			 <p><b>SOLID SEALING</b> TECHNOLOGY</p>	
REV.	APP'D	DATE	SCALE 1.25:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	7/19/2016	PART NO. FA30979 REV. C	WWW.SOLIDSEALING.COM	
C1	CW	2/10/2023	CO7160005-13		ENG APPR.	MH	7/20/2016		SALES DWG NO. FA30979SL REV. C1	

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**