


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA31289	COPPER	100 AMPS
FA13289-02	304 STN STL	6.5 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	125KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-55°C TO 450°C

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE

125KV FEEDTHRU



REV.	APP'D	DATE	SCALE 1:2	DIMENSIONS IN INCHES [mm]	DRAWN	JF	10/22/2014
B1	JF	11/17/2020	FTFL0038-12		ENG APPR.	JF	10/23/2014

PART NO. FA31289 REV. B

WWW.SOLIDSEALING.COM

SALES DWG NO. FA31289SL REV. B1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.