

FA33217-XXX

PART NUMBER

NUMBER OF SMPs IN FLANGE
eg. 1 THRU 4

AIR SIDE TERMINATION
eg. F=FULL
S= SMOOTH
L= LIMITED

VACUUM SIDE TERMINATION
eg. F=FULL
S= SMOOTH
L= LIMITED

Ø 1.58 [40.0]

KF25

.31 [7.9]

.38 [9.5]

Ø .38 [9.5]

Ø .38 [9.5]


PERFORMANCE SPECIFICATIONS	
VOLTAGE (DWV):	500V RMS
INSULATION RESISTANCE:	> 5000 MΩ
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C

LEAK RATE <1 X 10E-10 ATM-CC/SEC (He)

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE

50 OHM SMP IN KF25 FLANGE



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	12/18/2015
A2	CW	3/16/2021	COSM0004-11		ENG APPR.	JF	01/26/2016

PART NO. FA33217 REV. A

WWW.SOLIDSEALING.COM

SALES DWG NO. FA33217SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.