



PART NO.	AIR SIDE PLUG
FA33775	NO
KT33775	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE	500V DC
CURRENT	3.6 AMPS
PRESSURE	1 400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG	-260°C TO 230°C
TEMPERATURE WITH PLUG	-65°C TO 165°C

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</p>				<p>THIRD ANGLE PROJECTION</p> 		<p>TITLE</p> <p>DOUBLE ENDED BNC IN 1/2 NPT</p>		 <p>SOLID SEALING TECHNOLOGY</p>	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	4/12/2016	PART NO. FA33775 REV. B	WWW.SOLIDSEALING.COM
B1	CW	1/9/2025	COBN0037-12		ENG APPR.	MH	4/12/2016		SALES DWG NO. FA33775SL REV. B1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.