



PART NO.	AIR SIDE PLUG
FA33775	NO
KT33775	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE	500V DC
CURRENT	3.6 AMPS
PRESSURE	1 400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG	-260°C TO 230°C
TEMPERATURE WITH PLUG	-65°C TO 165°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA33775SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

DOUBLE ENDED BNC IN 1/2 NPT

PART NO. FA33775 REV. A

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	4/12/2016
A2	JF	06/13/2016	COBN0037-12		ENG APPR.	MH	4/12/2016

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.