



PERFORMANCE CHARACTERISTICS	
VOLTAGE	2700VRMS*
TEMPERATURE	-269°C TO 200°C (HIGH TEMP IS WITH SOCKETS INSTALLED AND LIMITED TO 1HR. CONSULT SST IF HIGHER TEMP BAKE OUT IS NEEDED)
LEAK RATE	<1 X 10E-10 ATM-CC/SEC (He)

\* VOLTAGE PERFORMANCE LIMITED BY STANDARD 7/16 COAXIAL PLUG.

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.					THIRD ANGLE PROJECTION 			TITLE: 50 OHM DBL ENDED 7/16 CONNECTOR			
REV.	APP'D	DATE	SCALE 1.25:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	8/24/2016	PART NO. FA33955 REV. B		SOLID SEALING TECHNOLOGY, INC.	
B1	JF	04/06/2020	CO7160005-14		ENG APPR.	MH	8/25/2016			SALES DWG NO. FA33955SL REV. B1	

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**