


PERFORMANCE SPECIFICATIONS	
VOLTAGE	375V DC
CURRENT	1 AMP
PRESSURE	1300 PSIG @ 20°C
TEMPERATURE	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE  
 25 PIN MICRO D CONNECTOR



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	7/5/2022
A1	MH	7/5/2022	MPCL486-11		ENG APPR.	MH	7/5/2022

PART NO. FA35400 REV. A

WWW.SOLIDSEALING.COM  
 SALES DWG NO. FA35400SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**