


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA36621	COPPER	100 AMPS
FA36621-02	MOLYBDENUM	50 AMPS
FA36621-03	NICKEL	30 AMPS
FA36621-04	304 STN STL	6.5 AMPS

PERFORMANCE SPECIFICATION	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1000 PSIG @20 °C
TEMPERATURE:	-269 °C TO 450 °C

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE

5KV FEEDTHROUGH



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	ET	05/17/2018
A1	JF	06/15/2020	FTST0223-11		ENG APPR.	JF	06/15/2020

PART NO. FA36621 REV. A

WWW.SOLIDSEALING.COM

SALES DWG NO. FA36621SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.