

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA36735	COPPER	16 AMPS
FA36735-02	MOLYBDENUM	8.5 AMPS
FA36735-03	NICKEL	5 AMPS
FA36735-04	304 STN STL	1.1 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	2 KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA36735SL REV. B1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 2KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. B

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	12/15/2017
B1	JF	10/29/2018	MPDC0044-1ST		ENG APPR.	JF	12/15/2017

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.