



- FIBER: 62.5/125µm MULTIMODE GRADED INDEX
- LEAK RATE <math>< 1 \times 10^{-9}</math> ATM-CC/SEC (He)
- AVAILABLE AIR SIDE PLUG FP35899
- AVAILABLE VACUUM SIDE PLUG FA36306

PERFORMANCE SPECIFICATIONS
.35 dB LOSS PER JUNCTION @ 850 nm TYPICAL, .5 dB MAX (@ ROOM TEMPERATURE)
OPERATING TEMPERATURE: -40°C TO 150°C
200°C BAKE OUT FOR 1 HOUR

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: ST TO ST FIBER OPTIC FEEDTHROUGH ADAPTER		WWW.SOLIDSEALING.COM 		
REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	01/22/2018	PART NO. FA36867 REV. A		SOLID SEALING TECHNOLOGY, INC.	
A2	JF	09/23/2019	FOFDN002-11		ENG APPR.	JF	01/25/2018			SALES DWG NO. FA36867SL REV. A2	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.