

- FIBER: 62.5/125 μ m MULTIMODE GRADED INDEX
- LEAK RATE <math>< 1 \times 10^{-9}</math> ATM-CC/SEC (He)
- AVAILABLE AIR SIDE PLUG FP35899
- AVAILABLE VACUUM SIDE PLUG FA36306

PERFORMANCE SPECIFICATIONS
.35 dB LOSS PER JUNCTION @ 850 nm TYPICAL, .5 dB MAX (@ ROOM TEMPERATURE)
OPERATING TEMPERATURE: -40°C TO 150°C
200°C BAKE OUT FOR 1 HOUR

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA36871SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

ST TO ST FIBER OPTIC
FEEDTHROUGH ADAPTER

PART NO. FA36871 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	01/31/2018
A2	JF	08/26/2019	FOFDN002-15		ENG APPR.	JF	01/31/2018

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.