

PERFORMANCE SPECIFICATIONS					
VOLTAGE:	1.5 KV DC				
CURRENT:	1 AMP				
TEMPERATURE WITHOUT PLUG:	-269°C TO 350°C				
TEMPERATURE WITH PLUG:	-65°C TO 165°C				

PART NO.	TYPE N AIR SIDE PLUG
FA36986	NO
KT36986	YES

									WWW.SOLIDSEALING.COM
	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.							50 OHM TYPE N TO SMA	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN	DRAWN	JF	08/31/2018	PART NO. FA36986 REV. A	SOLID SEALING TECHNOLOGY, INC.
A1	JF	08/31/2018	COTN0064-11	INCHES [mm]	ENG APPR.	JF	08/31/2018	TARTNO, TASU700 REV. A	SALES DWG NO. FA36986SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.