



PERFORMANCE SPECIFICATIONS
.3 dB LOSS PER JUNCTION @ 1550 nm TYPICAL, .45 dB MAX (@ ROOM TEMPERATURE)
OPERATING TEMPERATURE: -40°C TO 150°C
LEAK RATE <1 X 10E-9 ATM-CC/SEC (He)

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE SM FEEDTHROUGH, FC-FC			
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	11/01/2018	PART NO. FA37639 REV. D WWW.SOLIDSEALING.COM	
D1	JF	3/12/2021	FOFDN003-16		ENG APPR.	JF	11/01/2018		

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**