



PERFORMANCE SPECIFICATIONS	
MAX OPERATING VOLTAGE:	1 kV DC
MAX OPERATING CURRENT:	2.5 AMPS
MAX OPERATING PRESSURE:	3300 PSIG @ 20°C
TEMPERATURE RANGE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE: FEEDTHRU			
REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN INCHES [mm]	DRAWN	OG	11/12/2018	PART NO. FA38247 REV. A WWW.SOLIDSEALING.COM	
A2	OG	05/26/2020	FTCL0277-12		ENG APPR.	OG	02/04/2020		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.