


NOTES:

- 1- THIS FEEDTHRU MUST BE LASER WELDED.
- 2- FOR INDICATED PRESSURE PERFORMANCE, THE FEEDTHRU MUST BE MECHANICALLY BACKED UP AS SHOWN.



PERFORMANCE SPECIFICATIONS	
MAX OPERATING VOLTAGE:	3 kV DC
MAX OPERATING CURRENT:	2.5 AMPS
MAX OPERATING PRESSURE:	1300 PSIG @ 20°C
TEMPERATURE RANGE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 	TITLE: FEEDTHRU			SOLID SEALING TECHNOLOGY	
REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN INCHES [mm]	DRAWN	OG	11/13/2018	PART NO. FA38252 REV. A	WWW.SOLIDSEALING.COM
A2	OG	05/26/2020	FTCL0278-13	ENG APPR.	OG	02/04/2020	02/04/2020		SALES DWG NO. FA38252SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.