



PART NO.	AIR SIDE PLUG/ CABLE
FA40102	NO
KT40102	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	1KV DC
CURRENT:	2 AMPS
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-40°C TO 75°C

LEAK RATE < 1 X 10E-10 ATM-CC/SEC (He)

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE MICRODOT CONNECTOR			
REV.	APP'D	DATE	SCALE 5:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	9/16/2020	PART NO. FA40102 REV. B WWW.SOLIDSEALING.COM	
B1	JF	05/10/2024	COMC0014-22	ENG APPR.	MH	3/11/2021	SALES DWG NO. FA40102SL REV. B1		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.