


PERFORMANCE SPECIFICATIONS	
TRANSMISSION RANGE 80% MIN:	0.25 TO 4 MICRONS
PRESSURE:	160 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE:

SAPPHIRE VIEWPORT



REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	01/15/2020
B1	JF	02/20/2020	VPWD0014-25		ENG APPR.	JF	01/15/2020

PART NO. FA40254 REV. B

WWW.SOLIDSEALING.COM

SALES DWG NO. FA40254SL REV. B1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.